2000 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 2000 *Forest Products Journal*, volume 50, are listed both by subject and by author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus $5 handling charge per order. There is a charge of $6 for a copy of the 2000 *FPJ* Subject and Author Index.

ADHESIVES/ADHESION

Adhesive Bonding of Eastern Hemlock Glulam Panels With E-Glass/Vinyl Ester Reinforcement, R. Lopez-Anido, D.J. Gardner, and J.L. Hensley, 11/12:43-47 (No. 9073).

Bonding Moso Bamboo With Copolymer Resins Made of Biomass Residue Extracts With Phenol and Formaldehyde, C.-M. Chen, H.-C. Chen, and T.M.-Y. Liao, 9:70-74 (No. 9047).

Composting of Phenolic-Bonded Softwood Plywood Waste, D. Wiltcher, H. Borazjani, S.V. Diehl, and H.A. Stewart, 10:82-85 (No. 9046).

Durability of One-Part Polyurethane Bonds to Wood Improved by HMR Coupling Agent, C.B. Vick and E.A. Okkonen, 10:69-75 (No. 9031).

Effect of Finger Geometry and End Pressure on the Flexural Properties of Finger-Jointed Tropical African Hardwoods, J. Ayarkwa, Y. Hirashima, and Y. Sasaki, 11/12:53-63 (No. 9063).

Effect of Glue Type on Flexural and Tensile Properties of Finger-Jointed Tropical African Hardwoods, J. Ayarkwa, Y. Hirashima, Y. Sasaki, and K. Ando, 10:59-68 (No. 9067).

Gluability of Out-of-Service Utility Poles, H. Roliadi, C.Y. Hse, E.T. Choong, and T.F. Shupe, 10:76-81 (No. 9062).

Laboratory Apparatus for Applying Air-Sprayed Powdered Adhesive, T. Sellers, Jr., D.L. Butler, C.L. Griffin, D.E. Headley, and G.D. Miller, Jr., 5:88-90 (No. 9007).

Room-Temperature Laminating of CCA-Treated Lumber With Copolymer Resins Made of Biomass Extracts, C.-M. Chen and D.L. Nicholls, 3:81-86 (No. 8987).

Tannin-Based Resins Modified to Reduce Wood Adhesive Brittleness, A.P. Barbosa, E.B. Mano, and C.T. Andrade, 9:89-92 (No. 8919).

AIR AND WATER QUALITY

Biofiltration of Selected Monoterpenes Found in Southern Yellow Pine Wood Emissions, S.V. Diehl, B. Saileela, L.L. Wasson, and A. Borazjani, 1:43-48 (No. 8908).

Empirical Prediction of VOC Emissions From Drying Southern Yellow Pine Lumber, R. Shmulsky and L.L. Ingram, Jr., 6:61-63 (No. 9024).

End-Grain Influence on VOC Emissions From Kiln-Drying Loblolly Pine, R. Shmulsky, 5:21-23 (No. 9044).

Influence of Lumber Dimension on VOC Emissions From Kiln-Drying Loblolly Pine Lumber, R. Shmulsky, 3:63-66 (No. 9043).

The Measurement of Volatile Organic Emissions From Drying Southern Pine Lumber in a Laboratory-Scale Kiln, L.L. Ingram, Jr., R. Shmulsky, A.T. Dalton, F.W. Taylor, and M.C. Templeton, 4:91-94 (No. 8990).

Press Volatile Organic Compound Emissions as a Function of Wood Particleboard Processing Parameters, A. Barry, D. Corneau, and R. Lovell, 10:35-42 (No. 9033).

Surface Absorption, Surface Roughness, and Formaldehyde Emission of Turkish Medium Density Fiberboard, T. Akbulut, S. Hiziroglu, and N. Ayrilmis, 6:45-48 (No. 9002).

VOC Emissions From Douglas-fir: Comparing a Commercial and a Laboratory Kiln, M.R. Lavery and M.R. Milota, 7/8:39-47 (No. 8958).

ANATOMY AND QUALITY

Comparative Analysis of the Quality of Sawlogs From 35-, 40-, and 50-Year-Old Loblolly Pine Plantation Stands, H.F. Carino and E.J. Biblis, 11/12:48-52 (No. 9025).

Incidence of Defects by Tree Characteristics in Radiata Pine Random-Width Boards, R. Gazo, R. Beauregard, M. Kimberley, and D. McConchie, 6:83-89 (No. 8954).

Influence of Pruning and Log Height Class on Incidence of Defects in Radiata Pine Random-Width Boards, R. Gazo, R. Beauregard, and M. Kimberley, 9:28-31 (No. 8977).

Mechanical Properties of Stemwood and Limbwood of Seed Orchard Loblolly Pine, R.H. McAlister, H.R. Powers, and W.D. Pepper, 10:91-94 (No. 8995).

CHEMISTRY AND CHEMICAL MODIFICATION

Aldehyde Emissions From Particleboard and Medium Density Fiberboard Products, M.G.D. Baumann, L.F. Lorenz, S.A. Batterman, and G.-Z. Zhang, 9:75-82 (No. 9064).

Biofiltration of Selected Monoterpenes Found in Southern Yellow Pine Wood Emissions, S.V. Diehl, B. Saileela, L.L. Wasson, and A. Borazjani, 1:43-48 (No. 8908).

Comparison of the Absorptive Capacity of Shavings of Western Juniper, Western Redcedar, and Douglas-fir for Animal Bedding, E.G. Pearson, S. Leavengood, and J.E. Reeb, 6:57-60 (No. 9019).

Compatibility of Some Tropical Hardwoods Species With Portland Cement Using Isothermal Calorimetry, M.M. Alberto, E. Mougel, and A. Zoulalian, 9:83-88 (No. 9015).

COMPOSITES AND ENGINEERED PRODUCTS

Adhesive Bonding of Eastern Hemlock Glulam Panels With E-Glass/Vinyl Ester Reinforcement, R. Lopez-Anido, D.J. Gardner, and J.L. Hensley, 11/12:43-47 (No. 9073).

Aldehyde Emissions From Particleboard and Medium Density Fiberboard Products, M.G.D. Baumann, L.F. Lorenz, S.A. Batterman, and G.-Z. Zhang, 9:75-82 (No. 9064).

Bonding Moso Bamboo With Copolymer Resins Made of Biomass Residue Extracts With Phenol and Formaldehyde, C.-M. Chen, H.-C. Chen, and T.M.-Y. Liao, 9:70-74 (No. 9047).

Cement-Bonded Particleboards Using CCA-Treated Wood Removed From Service, C. Huang and P.A. Cooper, 6:49-56 (No. 9022).

Compatibility of Some Tropical Hardwoods Species With Portland Cement Using Isothermal Calorimetry, M.M. Alberto, E. Mougel, and A. Zoulalian, 9:83-88 (No. 9015).

Computerized Dynamic Swellometer Evaluation of Oriented Strand Products, Y.-S. Oh, L.S. Sites, T. Sellers, Jr., and D.D. Nicholas, 3:35-38 (No. 8979).

The Effect of Species and Species Distribution on the Layer Characteristics of OSB, S. Wang and P.M. Winistorfer, 4:37-44 (No. 8989).

Effect of Weathering on Surface Quality and Structural Properties of Six Species of Untreated Commercial Plywood Siding After 6 Years of Exposure in Alabama, E.J. Biblis, 5:47-50 (No. 8957).

Five-Point Bending Test for Determination of Edgewise Shear in Structural Panels, K. Fridley and L. French, 5:43-46 (No. 9009).

Flexural Properties of Southern Pine Plywood Overlaid With Fiberglass-Reinforced Plastic, E.J. Biblis and H.F. Carino, 4:34-36 (No. 8998).

Friction Coefficients of Wood-Based Structural Composites, L. Bejo, E.M. Lang, and T. Fodor, 3:39-43 (No. 8913).

Hot-Pressing of Oriented Strandboard by Step-Closure, S. Wang, P.M. Winistorfer, W.W. Moschler, and C. Helton, 3:28-34 (No. 8999).

Influence of Percent Alignment and Shelling Ratio on Linear Expansion of Oriented Strandboard: A Model Investigation, W. Xu, 7/8:88-93 (No. 9012).

Influence of Percent Alignment and Shelling Ratio on Modulus of Elasticity of Oriented Strandboard: A Model Investigation, W. Xu, 10:43-47 (No. 9023).

An Integrated Model of the Effect of Processing Parameters on the Strength of Oriented Strand Wood Products, D. Barnes, 11/12:33-42 (No. 9032).

Mechanics of Routing Medium Density Fiberboard, S. Engin, Y. Altintas, and F. Ben Amara, 9:65-69 (No. 9011).

Pilot Plant Evaluation of Steam-Injection Pressing for LVL and Plywood Products, G.E. Troughton and C. Lum, 1:25-28 (No. 8972).

Press Volatile Organic Compound Emissions as a Function of Wood Particleboard Processing Parameters, A. Barry, D. Corneau, and R. Lovell, 10:35-42 (No. 9033).

Recycled CCA-Treated Lumber in Flakeboards: Evaluation of Adhesives and Flakes, F. Mengeloglu and D.J. Gardner, 2:41-45 (No. 8925).

Recycled Thermoplastics Reinforced With Renewable Lignocellulosic Materials, T. Sellers, Jr., G.D. Miller, Jr., and M. Katabian, 5:24-28 (No. 8991).

Small-Diameter Log Evaluation for Value-Added Structural Applications, R. Wolfe and C. Moseley, 10:48-58 (No. 8996).

Surface Absorption, Surface Roughness, and Formaldehyde Emission of Turkish Medium Density Fiberboard, T. Akbulut, S. Hiziroglu, and N. Ayrilmis, 6:45-48 (No. 9002).

Toughness Properties for Several Composite Lumber Materials, J.J. Janowiak and S.W. Bukowski, 5:51-54 (No. 9020).

Deterioration/Degradation and Preservation

Canadian Bluestain Fungi: Variation in Tolerance to Sapstain Control Biocides, J.W. Dubois, A. Byrne, and J.E. Clark, 1:60-66 (No. 8967).

Capping and Chemical Treatment of Douglas-fir Piling to Prevent Pile Top Decay: A 13-Year Test, R.G. Rhatigan, P.F. Schneider, M.A. Newbill, and J.J. Morrell, 7/8:66-70 (No. 8813).

Decay Resistance of Out-of-Service Utility Poles as Related to the Distribution of Residual Creosote Content, H. Roliadi, C.Y. Hse, E.T. Choong, and T.F. Shupe, 11/12:64-68 (No. 9037).

Effect of Weathering on Surface Quality and Structural Properties of Six Species of Untreated Commercial Plywood Siding After 6 Years of Exposure in Alabama, E.J. Biblis, 5:47-50 (No. 8957).

The Effects of Different Kerfing and Center-Boring Treatments on the Checking of ACQ Treated Pine Posts Exposed to the Weather, P.D. Evans, R. Wingate-Hill, and S.C. Barry, 2:59-64 (No. 8962).

The Effects of Supercritical CO_2 on the Bending Properties of Four Refractory Wood Species, M.E. Anderson, R.J. Leichti, and J.J. Morrell, 11/12:85-93 (No. 9045).

A Field Trial of Pigment-Emulsified Creosote: 11 Year Data, J.W. Creffield, H. Greaves, N. Chew, and N.-K. Nguyen, 6:77-82 (No. 8985).

Five-Year Field Trials Using Preservative-Treated, Second Growth Douglas-fir Exposed in Ground Contact in Australia, R.C. De Groot, D.M. Crawford, J. Norton, and J. Keith, 2:46-53 (No. 8948).

Gluability of Out-of-Service Utility Poles, H. Roliadi, C.Y. Hse, E.T. Choong, and T.F. Shupe, 10:76-81 (No. 9062).

Incidence of Wood-Destroying Organisms in Oregon Residential Structures, M. Mankowski and J.J. Morrell, 1:49-52 (No. 8935).

Laboratory Evaluation of Microwaves for Control of the Western Drywood Termite, V.R. Lewis, A.B. Power, and M.I. Haverty, 5:79-87 (No. 9006).

Natural Decay Resistance of Heartwood From Dead, Standing Yellow-Cedar Trees: Laboratory Evaluations, R.C. De Groot, B. Woodward, and P.E. Hennon, 1:53-59 (No. 8960).

Preservative Movement From Douglas-fir Decking and Timbers Treated With Ammoniacal Copper Zink Arsenate Using Best Management Practices, J.J. Morrell and R. Rhatigan, 2:54-58 (No. 8924).

Treatability of U.S. Wood Species With Pigment-Emulsified Creosote, D.M. Crawford, R.C. De Groot, J.B. Watkins, H. Greaves, K.J. Schmalzl, and T.L. Syers, 1:29-35 (No. 8968).

Drying and Storage

Changes in Moisture, Soluble Carbohydrate, and Bacterial Numbers During Water Storage of Pine, M.A. Powell, J.F. Webber, and R.A. Eaton, 3:74-80 (No. 8994).

Comparison of Shrinkage, Checking, and Absorbed Energy in Impact Bending of Korean Ash Squares Dried by a Radio-Frequency/Vacuum Process and a Conventional Kiln, N.-H. Lee and H.-S. Jung, 2:69-72 (No. 8867).

Effect of End-Covering and Low Pressure Steam Explosion Treatment on Drying Rate and Checking During Radio-Frequency/Vacuum Drying of Japanese Cedar Log Cross Sections, N.-H. Lee and K. Hayashi, 2:73-78 (No. 8916).

Empirical Prediction of VOC Emissions From Drying Southern Yellow Pine Lumber, R. Shmulsky and L.L. Ingram, Jr., 6:61-63 (No. 9024).

End-Grain Influence on VOC Emissions From Kiln-Drying Loblolly Pine, R. Shmulsky, 5:21-23 (No. 9044).

The Equilibrium Moisture Content of Common U.K. Species at Three Conditions of Temperature and Relative Humidity, K. Ahmet, G. Dai, R. Tomlin, P. Kaczmar, and S. Riddiough, 6:64-68 (No. 9018).

Influence of Drying Schedule on VOC Emissions From Kiln-Drying Loblolly Pine Lumber, R. Shmulsky, 4:45-48 (No. 8894).

VOC Emissions From Douglas-fir: Comparing a Commercial and a Laboratory Kiln, M.R. Lavery and M.R. Milota, 7/8:39-47 (No. 8958).

Warp and Shrinkage of Hem-fir Stud Lumber Dried at Conventional and High Temperatures, M.R. Milota, 11/12:79-84 (No. 9038).

Energy Generation and Conservation

An Integrated Model of the Effect of Processing Parameters on the Strength of Oriented Strand Wood Products, D. Barnes, 11/12:33-42 (No. 9032).

Engineering and Mechanical Properties

Comparison of Actual vs. Simulated Failure Distributions of Flexural Wood Specimens Subject to 5-Day Load Sequences, Z. Cai, D.V. Rosowsky, M.O. Hunt, and K.J. Fridley, 1:74-80 (No. 8926).

Effect of Glue Type on Flexural and Tensile Properties of Finger-Jointed Tropical African Hardwoods, J. Ayarkwa, Y. Hirashima, Y. Sasaki, and K. Ando, 10:59-68 (No. 9067).

Engineering Evaluation of 55-Year-Old Timber Columns Recycled From an Indus-

trial Military Building, R.H. Falk, D. Green, D. Rammer, and S.F. Lantz, 4:71-76 (No. 8939).

Evaluation of Lumber Properties by Applying Stress Waves to Larch Logs Grown in Korea, S.S. Jang, 3:44-48 (No. 8988).

Influence of Percent Alignment and Shelling Ratio on Modulus of Elasticity of Oriented Strandboard: A Model Investigation, W. Xu, 10:43-47 (No. 9023).

Mechanical Properties of Stemwood and Limbwood of Seed Orchard Loblolly Pine, R.H. McAlister, H.R. Powers, and W.D. Pepper, 10:91-94 (No. 8995).

Nondestructive Measurement of Wood Properties by Using Near-Infrared Laser Radiation, S. Tsuchikawa, T. Takahashi, and S. Tsutsumi, 1:81-86 (No. 8871).

Potential Use of a Piezoelectric Wire Sensor for Monitoring the Bending Vibrations of Logs, D. Ouis, 4:61-64 (No. 8855).

Static and Vibration Moduli of Elasticity of Salvaged and New Joists, Z. Cai, M.O. Hunt, R.J. Ross, and L.A. Soltis, 2:35-40 (No. 8928).

Stress-Wave Analysis of Douglas-fir Logs for Veneer Properties, R.C. Rippy, F.G. Wagner, T.M. Gorman, H.D. Layton, and T. Bodenheimer, 4:49-52 (No. 8966).

Wood Floor Vibrational Performance as Affected by MSR vs. VSR Lumber E-Distribution, A.C. Wilson, F.E. Woeste, and D.J. Dolan, 4:53-60 (No. 8852).

Furniture and Hardwood Veneer/Plywood

Beyond Yield Improvement: Selected Marketing Aspects of Character-Marked Furniture, M.S. Bumgardner, R.J. Bush, and C.D. West, 9:51-58 (No. 9048).

Panel Products: A Perspective From Furniture and Cabinet Manufacturers in the Southern United States, Q. Wu and R.P. Vlosky, 9:45-50 (No. 8993).

Species, Furniture Type, and Market Factors Influencing Furniture Sales in Southern Germany, T. Kärki, 4:85-90 (No. 8984).

A Structural Design Model For Sofa Seat Frames Equipped With Sinusoidal-Type Springs, J. Zhang, F.-C. Lin, C. Eckelman, and H. Gibson, 3:49-57 (No. 8907).

Virtual Interference Detection With Case Goods Assemblies, D. Cormier and K. Unnanon, 5:75-78 (No. 9014).

Lumber Production

An Assessment of Pallet Lumber Supply and Manufacturing in Colorado, K.H. Mackes and D.L. Lynch, 4:77-80 (No. 8938).

Characteristics of the Eastern "Grade" Hardwood Sawmilling Industry, W. Luppold, J. Baumgras, and G. Barrett, 9:23-27 (No. 9065).

Green Dimensioning Below-Grade Red Oak Logs: A Minnesota Case Study, S.M. Bratkovich, J.S. Gephart, P. Peterson, and R.H. Bartz, 2:65-68 (No. 8808).

Incidence of Defects by Tree Characteristics in Radiata Pine Random-Width Boards, R. Gazo, R. Beauregard, M. Kimberley, and D. McConchie, 6:83-89 (No. 8954).

Influence of Pruning and Log Height Class on Incidence of Defects in Radiata Pine Random-Width Boards, R. Gazo, R. Beauregard, and M. Kimberley, 9:28-31 (No. 8977).

Mechanical Grading of Lumber Sawn From Small-Diameter Lodgepole Pine, Ponderosa Pine, and Grand Fir Trees From Northern Idaho, R.G. Erikson, T.M. Gorman, D.W. Green, and D. Graham, 7/8:59-65 (No. 8909).

Pallet and Component Parts From Small-Diameter Red Oak Bolts, J.R. Serrano and D. Cassens, 3:67-73 (No. 8725).

Some Implications of Remanufacturing Hardwood Lumber, C.J. Gatchell, R.E. Thomas, and E.S. Walker, 2:79-89 (No. 8974).

Validation of a CT-Based Simulator Against a Sawmill Yield, S. Chiorescu and A. Grönlund, 6:69-76 (No. 9027).

Warp and Shrinkage of Hem-fir Stud Lumber Dried at Conventional and High Temperatures, M.R. Milota, 11/12:79-84 (No. 9038).

Marketing, Management, and Economics

Assessing the Business Environment for the Forest Products Industry in the Northeast, M.E. Carroll, V.A. Luzadis, J.E. Wagner, and D.W. Floyd, 5:61-62 (No. 8982).

An Assessment of Pallet Lumber Supply and Manufacturing in Colorado, K.H. Mackes and D.L. Lynch, 4:77-80 (No. 8938).

Beyond Yield Improvement: Selected Marketing Aspects of Character-Marked Furniture, M.S. Bumgardner, R.J. Bush, and C.D. West, 9:51-58 (No. 9048).

Characteristics of the Eastern "Grade" Hardwood Sawmilling Industry, W. Luppold, J. Baumgras, and G. Barrett, 9:23-27 (No. 9065).

EDI and Barcoding in the Homecenter Industry: 1992 vs. 1998, C.A. Roadcap, P.M. Smith, and R.P. Vlosky, 9:32-38 (No. 9051).

Forest Products Exporting and the Internet: Current Use Figures and Implementation Issues, O.T. Pitis and R.P. Vlosky, 10:23-29 (No. 9030).

Issues Affecting the Interpretation of Eastern Hardwood Resource Statistics, W.G. Luppold and W.H. McWilliams, 4:21-24 (No. 9005).

Length Effect in Prefabricated Wood I-Joists, D.J. Sharp, S.K. Suddarth, and C. Beaulieu, 5:29-42 (No. 8849).

Manufacturing Solid Wood Products From Used Utility Poles: An Economic Feasibility Study, S.A. King and D.K. Lewis, 11/12: 69-78 (No. 9021).

Marketing and Business Assistance Needs Perceived by Tennessee Forest Products Firms, K. Jensen and G. Pompelli, 7/8:48-54 (No. 9026).

The Pallet Industry in the Southern United States, M.A. Dunn, R.P. Vlosky, and T.F. Shupe, 10:30-34 (No. 9050).

Panel Products: A Perspective From Furniture and Cabinet Manufacturers in the Southern United States, Q. Wu and R.P. Vlosky, 9:45-50 (No. 8993).

Perceptions of Wood in the Highway Infrastructure Market, R.L. Smith, W.E. Spradlin, D.R. Alderman, Jr., and E. Cesa, 6:23-31 (No. 9016).

Profiling Existing Markets: The Illinois Secondary Solid Wood Products Industry, J.C. Mangun and J.E. Phelps, 5:55-60 (No. 9003).

Research Challenges for Structural Use of Small-Diameter Round Timbers, R. Wolfe, 2:21-29 (No. 8963).

Small-Diameter Log Evaluation for Value-Added Structural Applications, R. Wolfe and C. Moseley, 10:48-58 (No. 8996).

Southern Forest Resource Assessment Using the Subregional Timber Supply (SRTS) Model, R.C. Abt, F.W. Cubbage, and G. Pacheco, 4:25-33 (No. 8978).

Species, Furniture Type, and Market Factors Influencing Furniture Sales in Southern Germany, T. Kärki, 4:85-90 (No. 8984).

Status of Electronic Data Interchange in the Forest Products Industry, C.A. Dupuy and R.P. Vlosky, 6:32-38 (No. 9017).

Web Presence of U.S. Primary Wood Products Exporters, O.T. Pitis and R.P. Vlosky, 7/8:55-58 (No. 9041).

Why Forest Products Companies May Need to Hold Timberland, R. Yin, T.G. Harris, and B. Izlar, 9:39-44 (No. 9036).

Milling and Machining

Effect of Finger Geometry and End Pressure on the Flexural Properties of Finger-Jointed Tropical African Hardwoods, J. Ayarkwa, Y. Hirashima, and Y. Sasaki, 11/12:53-63 (No. 9063).

Mechanics of Routing Medium Density Fiberboard, S. Engin, Y. Altintas, and F. Ben Amara, 9:65-69 (No. 9011).

On the Cutting Performance of Diamond-Coated Cemented Carbide Tools Pretreated With Murakami/H_2O_2-H_2SO_4 Solution, T.

Morita, J.Y. Sheikh-Ahmad, K. Banshoya, T. Tsutsumoto, and Y. Murase, 1:67-73 (No. 8971).

Orthogonal Cutting Mechanics of Medium Density Fiberboards, J. Dippon, H. Ren, F. Ben Amara, and Y. Altintas, 7/8:25-30 (No. 9010).

The Use of Process Monitoring Techniques on a CNC Wood Router. Part 1. Sensor Selection, R.L. Lemaster, L. Lu, and S. Jackson, 7/8:31-38 (No. 8917).

The Use of Process Monitoring Techniques on a CNC Wood Router. Part 2. Use of a Vibration Accelerometer to Monitor Tool Wear and Workpiece Quality, R.L. Lemaster, L. Lu, and S. Jackson, 9:59-64 (No. 8918).

Validation of a CT-Based Simulator Against a Sawmill Yield, S. Chiorescu and A. Grönlund, 6:69-76 (No. 9027).

Physics and Moisture Relations

Detection of Transverse Moisture Gradients in Timber by Measurements of Capacitance Using a Multiple-Electrode Arrangement, S. Jazayeri and K. Ahmet, 11/12:27-32 (No. 9084).

The Effects of Supercritical CO_2 on the Bending Properties of Four Refractory Wood Species, M.E. Anderson, R.J. Leichti, and J.J. Morrell, 11/12:85-93 (No. 9045).

The Equilibrium Moisture Content of Common U.K. Species at Three Conditions of Temperature and Relative Humidity, K. Ahmet, G. Dai, R. Tomlin, P. Kaczmar, and S. Riddiough, 6:64-68 (No. 9018).

Influence of Percent Alignment and Shelling Ratio on Linear Expansion of Oriented Strandboard: A Model Investigation, W. Xu, 7/8:88-93 (No. 9012).

Juvenile Wood Effect in Red Alder: Analysis of Physical and Mechanical Data to Delineate Juvenile and Mature Wood Zones, J.W. Evans, II, J.F. Senft, and D.W. Green, 7/8: 75-87 (No. 8811).

Use of an Air Pressure Method for Detection and Mapping of Highly Permeable Ponderosa Pine, B.L. Wallace and E.L. Schmidt, 7/8:71-74 (No. 8986).

Process Control/ Quality Control

Differentiation of Knots, Distorted Grain, and Clear Wood by Radio-Frequency Scanning, P.H. Steele, L. Kumar, and R. Shmulsky, 3:58-62 (No. 8981).

The Use of Process Monitoring Techniques on a CNC Wood Router. Part 2. Use of a Vibration Accelerometer to Monitor Tool Wear and Workpiece Quality, R.L. Lemaster, L. Lu, and S. Jackson, 9:59-64 (No. 8918).

Recycling and Residue Utilization

Bonding Moso Bamboo With Copolymer Resins Made of Biomass Residue Extracts With Phenol and Formaldehyde, C.-M. Chen, H.-C. Chen, and T.M.-Y. Liao, 9:70-74 (No. 9047).

Cement-Bonded Particleboards Using CCA-Treated Wood Removed From Service, C. Huang and P.A. Cooper, 6:49-56 (No. 9022).

Comparison of the Absorptive Capacity of Shavings of Western Juniper, Western Redcedar, and Douglas-fir for Animal Bedding, E.G. Pearson, S. Leavengood, and J.E. Reeb, 6:57-60 (No. 9019).

Composting of Phenolic-Bonded Softwood Plywood Waste, D. Wiltcher, H. Borazjani, S.V. Diehl, and H.A. Stewart, 10:82-85 (No. 9046).

Engineering Evaluation of 55-Year-Old Timber Columns Recycled From an Industrial Military Building, R.H. Falk, D. Green, D. Rammer, and S.F. Lantz, 4:71-76 (No. 8939).

Manufacturing Solid Wood Products From Used Utility Poles: An Economic Feasibility Study, S.A. King and D.K. Lewis, 11/12: 69-78 (No. 9021).

Solid Wood Received and Marketed by Virginia's Landfill Facilities, D.R. Alderman, Jr. and R.L. Smith, 6:39-44 (No. 9004).

Testing and Test Methodology

Five-Point Bending Test for Determination of Edgewise Shear in Structural Panels, K. Fridley and L. French, 5:43-46 (No. 9009).

Timber Production and Harvesting

Analysis of Changes in Eastern National Forest Timber Sales Between 1985 and 1997, W.G. Luppold and J.E. Baumgras, 1:87-93 (No. 8952).

Assessing the Operational Cost of Streamside Management Zones, R. Kluender, R. Weih, M. Corrigan, and J. Pickett, 2:30-34 (No. 8782).

Comparative Analysis of the Quality of Sawlogs From 35-, 40-, and 50-Year-Old Loblolly Pine Plantation Stands, H.F. Carino and E.J. Biblis, 11/12:48-52 (No. 9025).

Control of Log End Checks During Bucking With a Modified Single-Grip Harvester, J. Eronen, A. Asikainen, J. Uusitalo, and L. Sikanen, 4:65-70 (No. 8965).

Economic Potential of Short-Rotation Woody Crops on Agricultural Land for Pulp Fiber Production in the United States, R.J. Alig, D.M. Adams, B.A. McCarl, and P.J. Ince, 5:67-74 (No. 8980).

Influence of Pruning and Log Height Class on Incidence of Defects in Radiata Pine Random-Width Boards, R. Gazo, R. Beauregard, and M. Kimberley, 9:28-31 (No. 8977).

Issues Affecting the Interpretation of Eastern Hardwood Resource Statistics, W.G. Luppold and W.H. McWilliams, 4:21-24 (No. 9005).

Matching Skidder Size to Wood Harvested to Increase Hardwood Fiber Availability: A Case Study, C.B. LeDoux, 10:86-90 (No. 9049).

Production and Costs of the Chambers Delimbinator in First Thinning of Pine Planatations, S.T. Mooney, K.D. Boston, and W.D. Greene, 4:81-84 (No. 9001).

Scar Closure and Future Timber Value Losses From Thinning Damage in Western Oregon, H.-S. Han, L.D. Kellogg, G.M. Filip, and T.D. Brown, 1:36-42 (No. 8836).

Southern Forest Resource Assessment Using the Subregional Timber Supply (SRTS) Model, R.C. Abt, F.W. Cubbage, and G. Pacheco, 4:25-33 (No. 8978).

The Use of a Geographic Information System in Harvest Landing Location for Ground-Based Skidding Operations, R. Kluender, R. Weih, M. Corrigan, and J. Pickett, 3:87-92 (No. 8791).

Why Forest Products Companies May Need to Hold Timberland, R. Yin, T.G. Harris, and B. Izlar, 9:39-44 (No. 9036).

Wood and The Environment

Influence of Drying Schedule on VOC Emissions From Kiln-Drying Loblolly Pine Lumber, R. Shmulsky, 4:45-48 (No. 8894).

USDA Forest Service, Bureau of Land Management, and State Forester Perspectives on Certification, R.P. Vlosky, 3:21-27 (No. 8823).

Feature Articles

Development of Softwood Plantation Timber in the United States, S.L. Floyd and N.P. Kutscha, 11/12:20-24 (No. 9060).

Developments in Performance-Based Building Codes and Standards, G.C. Foliente, 7/8:12-21 (No. 9057).

Emissions From Wood Drying: The Science and the Issues, M.R. Milota, 6:10-20 (No. 9056).

The Formosan Subterranean Termite in Louisiana: Implications for the Forest Products Industry, T.F. Shupe and M.A. Dunn, 5:10-18 (No. 9055).

SIPs: Overcoming the Elements, J.M. Tracy, 3:12-18 (No. 9054).

Trees are the Answer, P. Moore, 10:12-19 (No. 9059).

Tropical Deforestation: Uncovering the Story, J.L. Bowyer, 2:10-18 (No. 9053).

Wood in the Third Millennium, W.R.J. Sutton, 1:12-21 (No. 9052).

Wood Preservation: Trends of Today That Will Influence the Industry Tomorrow, A.F. Preston, 9:12-19 (No. 9058).

A

Abt, R.C., F.W. Cubbage, and G. Pacheco, Southern Forest Resource Assessment Using the Subregional Timber Supply (SRTS) Model, 4:25-33 (No. 8978).

Adams, D.M., see Alig, R.J.

Ahmet, K., G. Dai, R. Tomlin, P. Kaczmar, and S. Riddiough, The Equilibrium Moisture Content of Common U.K. Species at Three Conditions of Temperature and Relative Humidity, 6:64-68 (No. 9018).

Ahmet, K., see Jazayeri, S.

Akbulut, T., S. Hiziroglu, and N. Ayrilmis, Surface Absorption, Surface Roughness, and Formaldehyde Emission of Turkish Medium Density Fiberboard, 6:45-48 (No. 9002).

Alberto, M.M., E. Mougel, and A. Zoulalian, Compatibility of Some Tropical Hardwoods Species With Portland Cement Using Isothermal Calorimetry, 9:83-88 (No. 9015).

Alderman, D.R., Jr. and R.L. Smith, Solid Wood Received and Marketed by Virginia's Landfill Facilities, 6:39-44 (No. 9004).

Alderman, D.R., Jr., see Smith, R.L.

Alig, R.J., D.M. Adams, B.A. McCarl, and P.J. Ince, Economic Potential of Short-Rotation Woody Crops on Agricultural Land for Pulp Fiber Production in the United States, 5:67-74 (No. 8980).

Altintas, Y., see Dippon, J.

Altintas, Y., see Engin, S.

Anderson, M.E., R.J. Leichti, and J.J. Morrell, The Effects of Supercritical CO_2 on the Bending Properties of Four Refractory Wood Species, 11/12:85-93 (No. 9045).

Ando, K., see Ayarkwa, J.

Andrade, C.T., see Barbosa, A.P.

Asikainen, A., see Eronen, J.

Ayarkwa, J., Y. Hirashima, and Y. Sasaki, Effect of Finger Geometry and End Pressure on the Flexural Properties of Finger-Jointed Tropical African Hardwoods, 11/12:53-63 (No. 9063).

Ayarkwa, J., Y. Hirashima, Y. Sasaki, and K. Ando, Effect of Glue Type on Flexural and Tensile Properties of Finger-Jointed Tropical African Hardwoods, 10:59-68 (No. 9067).

Ayrilmis, N., see Akbulut, T.

B

Banshoya, K., see Morita, T.

Barbosa, A.P., E.B. Mano, and C.T. Andrade, Tannin-Based Resins Modified to Reduce Wood Adhesive Brittleness, 9:89-92 (No. 8919).

Barnes, D., An Integrated Model of the Effect of Processing Parameters on the Strength of Oriented Strand Wood Products, 11/12: 33-42 (No. 9032).

Barrett, G., see Luppold, W.

Barry, A., D. Corneau, and R. Lovell, Press Volatile Organic Compound Emissions as a Function of Wood Particleboard Processing Parameters, 10:35-42 (No. 9033).

Barry, S.C., see Evans, P.D.

Bartz, R.H., see Bratkovich, S.M.

Batterman, S.A., see Baumann, M.G.D.

Baumann, M.G.D., L.F. Lorenz, S.A. Batterman, and G.-Z. Zhang, Aldehyde Emissions From Particleboard and Medium Density Fiberboard Products, 9:75-82 (No. 9064).

Baumgras, J., see Luppold, W.

Baumgras, J.E., see Luppold, W.G.

Beaulieu, C., see Sharp, D.J.

Beauregard, R., see Gazo, R.

Bejo, L., E.M. Lang, and T. Fodor, Friction Coefficients of Wood-Based Structural Composites, 3:39-43 (No. 8913).

Ben Amara, F., see Dippon, J.

Ben Amara, F., see Engin, S.

Biblis, E.J., Effect of Weathering on Surface Quality and Structural Properties of Six Species of Untreated Commercial Plywood Siding After 6 Years of Exposure in Alabama, 5:47-50 (No. 8957).

Biblis, E.J. and H.F. Carino, Flexural Properties of Southern Pine Plywood Overlaid With Fiberglass-Reinforced Plastic, 4:34-36 (No. 8998).

Biblis, E.J., see Carino, H.F.

Bodenheimer, T., see Rippy, R.C.

Borazjani, A., see Diehl, S.V.

Borazjani, H., see Wiltcher, D.

Boston, K.D., see Mooney, S.T.

Bowyer, J.L., Tropical Deforestation: Uncovering the Story, 2:10-18 (No. 9053).

Bratkovich, S.M., J.S. Gephart, P. Peterson, and R.H. Bartz, Green Dimensioning Below-Grade Red Oak Logs: A Minnesota Case Study, 2:65-68 (No. 8808).

Brown, T.D., see Han, H.-S.

Bukowski, S.W., see Janowiak, J.J.

Bumgardner, M.S., R.J. Bush, and C.D. West, Beyond Yield Improvement: Selected Marketing Aspects of Character-Marked Furniture, 9:51-58 (No. 9048).

Bush, R.J., see Bumgardner, M.S.

Butler, D.L., see Sellers, T., Jr.

Byrne, A., see Dubois, J.W.

C

Cai, Z., M.O. Hunt, R.J. Ross, and L.A. Soltis, Static and Vibration Moduli of Elasticity of Salvaged and New Joists, 2:35-40 (No. 8928).

Cai, Z., D.V. Rosowsky, M.O. Hunt, and K.J. Fridley, Comparison of Actual vs. Simulated Failure Distributions of Flexural Wood Specimens Subject to 5-Day Load Sequences, 1:74-80 (No. 8926).

Carino, H.F. and E.J. Biblis, Comparative Analysis of the Quality of Sawlogs From 35-, 40-, and 50-Year-Old Loblolly Pine Plantation Stands, 11/12:48-52 (No. 9025).

Carino, H.F., see Biblis, E.J.

Carroll, M.E., V.A. Luzadis, J.E. Wagner, and D.W. Floyd, Assessing the Business Environment for the Forest Products Industry in the Northeast, 5:61-62 (No. 8982).

Cassens, D., see Serrano, J.R.

Cesa, E., see Smith, R.L.

Chen, C.-M., H.-C. Chen, and T.M.-Y. Liao, Bonding Moso Bamboo With Copolymer Resins Made of Biomass Residue Extracts With Phenol and Formaldehyde, 9:70-74 (No. 9047).

Chen, C.-M. and D.L. Nicholls, Room-Temperature Laminating of CCA-Treated Lumber With Copolymer Resins Made of Biomass Extracts, 3:81-86 (No. 8987).

Chen, H.-C., see Chen, C.-M.

Chew, N., see Creffield, J.W.

Chiorescu, S. and A. Grönlund, Validation of a CT-Based Simulator Against a Sawmill Yield, 6:69-76 (No. 9027).

Choong, E.T., see Roliadi, H.

Clark, J.E., see Dubois, J.W.

Cooper, P.A., see Huang, C.

Cormier, D. and K. Unnanon, Virtual Interference Detection With Case Goods Assemblies, 5:75-78 (No. 9014).

Corneau, D., see Barry, A.

Corrigan, M., see Kluender, R.

Crawford, D.M., R.C. De Groot, J.B. Watkins, H. Greaves, K.J. Schmalzl, and T.L. Syers, Treatability of U.S. Wood Species With Pigment-Emulsified Creosote, 1:29-35 (No. 8968).

Crawford, D.M., see De Groot, R.C.

Creffield, J.W., H. Greaves, N. Chew, and N.-K. Nguyen, A Field Trial of Pigment-Emulsified Creosote: 11 Year Data, 6:77-82 (No. 8985).

Cubbage, F.W., see Abt, R.C.

D

Dai, G., see Ahmet, K.

Dalton, A.T., see Ingram, L.L., Jr.

De Groot, R.C., D.M. Crawford, J. Norton, and J. Keith, Five-Year Field Trials Using Preservative-Treated, Second Growth Douglas-fir Exposed in Ground Contact in Australia, 2:46-53 (No. 8948).

De Groot, R.C., B. Woodward, and P.E. Hennon, Natural Decay Resistance of Heartwood From Dead, Standing Yellow-Cedar Trees: Laboratory Evaluations, 1:53-59 (No. 8960).

De Groot, R.C., see Crawford, D.M.

Diehl, S.V., B. Saileela, L.L. Wasson, and A. Borazjani, Biofiltration of Selected Monoterpenes Found in Southern Yellow Pine Wood Emissions, 1:43-48 (No. 8908).

Diehl, S.V., see Wiltcher, D.

Dippon, J., H. Ren, F. Ben Amara, and Y. Altintas, Orthogonal Cutting Mechanics of Medium Density Fiberboards, 7/8:25-30 (No. 9010).

Dolan, D.J., see Wilson, A.C.

Dubois, J.W., A. Byrne, and J.E. Clark, Canadian Bluestain Fungi: Variation in Tolerance to Sapstain Control Biocides, 1:60-66 (No. 8967).

Dunn, M.A., R.P. Vlosky, and T.F. Shupe, The Pallet Industry in the Southern United States, 10:30-34 (No. 9050).

Dunn, M.A., see Shupe, T.F.

Dupuy, C.A. and R.P. Vlosky, Status of Electronic Data Interchange in the Forest Products Industry, 6:32-38 (No. 9017).

E

Eaton, R.A., see Powell, M.A.

Eckelman, C., see Zhang, J.

Engin, S., Y. Altintas, and F. Ben Amara, Mechanics of Routing Medium Density Fiberboard, 9:65-69 (No. 9011).

Erikson, R.G., T.M. Gorman, D.W. Green, and D. Graham, Mechanical Grading of Lumber Sawn From Small-Diameter Lodgepole Pine, Ponderosa Pine, and Grand Fir Trees From Northern Idaho, 7/8:59-65 (No. 8909).

Eronen, J., A. Asikainen, J. Uusitalo, and L. Sikanen, Control of Log End Checks During Bucking With a Modified Single-Grip Harvester, 4:65-70 (No. 8965).

Evans, J.W., II, J.F. Senft, and D.W. Green, Juvenile Wood Effect in Red Alder: Analysis of Physical and Mechanical Data to Delineate Juvenile and Mature Wood Zones, 7/8:75-87 (No. 8811).

Evans, P.D., R. Wingate-Hill, and S.C. Barry, The Effects of Different Kerfing and Center-Boring Treatments on the Checking of ACQ Treated Pine Posts Exposed to the Weather, 2:59-64 (No. 8962).

F

Falk, R.H., D. Green, D. Rammer, and S.F. Lantz, Engineering Evaluation of 55-Year-Old Timber Columns Recycled From an Industrial Military Building, 4:71-76 (No. 8939).

Filip, G.M., see Han, H.-S.

Floyd, S.L. and N.P. Kutscha, Development of Softwood Plantation Timber in the United States, 11/12:20-24 (No. 9060).

Floyd, D.W., see Carroll, M.E.

Fodor, T., see Bejo, L.

Foliente, G.C., Developments in Performance-Based Building Codes and Standards, 7/8:12-21 (No. 9057).

French, L., see Fridley, K.

Fridley, K. and L. French, Five-Point Bending Test for Determination of Edgewise Shear in Structural Panels, 5:43-46 (No. 9009).

Fridley, K.J., see Cai, Z.

G

Gardner, D.J., see Lopez-Anido, R.

Gardner, D.J., see Mengeloglu, F.

Gatchell, C.J., R.E. Thomas, and E.S. Walker, Some Implications of Remanufacturing Hardwood Lumber, 2:79-89 (No. 8974).

Gazo, R., R. Beauregard, and M. Kimberley, Influence of Pruning and Log Height Class on Incidence of Defects in Radiata Pine Random-Width Boards, 9:28-31 (No. 8977).

Gazo, R., R. Beauregard, M. Kimberley, and D. McConchie, Incidence of Defects by Tree Characteristics in Radiata Pine Random-Width Boards, 6:83-89 (No. 8954).

Gephart, J.S., see Bratkovich, S.M.

Gibson, H., see Zhang, J.

Gorman, T.M., see Erickson, R.G.

Gorman, T.M., see Rippy, R.C.

Graham, D., see Erikson, R.G.

Greaves, H., see Crawford, D.M.

Greaves, H., see Creffield, J.W.

Green, D., see Falk, R.H.

Green, D.W., see Erikson, R.G.

Green, D.W., see Evans, J.W., II

Greene, W.D., see Mooney, S.T.

Griffin, C.L., see Sellers, T., Jr.

Grönlund, A., see Chiorescu, S.

H

Han, H.-S., L.D. Kellogg, G.M. Filip, and T.D. Brown, Scar Closure and Future Timber Value Losses From Thinning Damage in Western Oregon, 1:36-42 (No. 8836).

Harris, T.G., see Yin, R.

Haverty, M.I., see Lewis, V.R.

Hayashi, K., see Lee, N.-H.

Headley, D.E., see Sellers, T., Jr.

Helton, C., see Wang, S.

Hennon, P.E., see De Groot, R.C.

Hensley, J.L., see Lopez-Anido, R.

Hirashima, Y., see Ayarkwa, J.

Hiziroglu, S., see Akbulut, T.

Hse, C.Y., see Roliadi, H.

Huang, C. and P.A. Cooper, Cement-Bonded Particleboards Using CCA-Treated Wood Removed From Service, 6:49-56 (No. 9022).

Hunt, M.O., see Cai, Z.

I

Ince, P.J., see Alig, R.J.

Ingram, L.L., Jr., R. Shmulsky, A.T. Dalton, F.W. Taylor, and M.C. Templeton, The Measurement of Volatile Organic Emissions From Drying Southern Pine Lumber in a Laboratory-Scale Kiln, 4:91-94 (No. 8990).

Ingram, L.L., Jr., see Shmulsky, R.

Izlar, B., see Yin, R.

J

Jackson, S., see Lemaster, R.L.

Jang, S.S., Evaluation of Lumber Properties by Applying Stress Waves to Larch Logs Grown in Korea, 3:44-48 (No. 8988).

Janowiak, J.J. and S.W. Bukowski, Toughness Properties for Several Composite Lumber Materials, 5:51-54 (No. 9020).

Jazayeri, S. and K. Ahmet, Detection of Transverse Moisture Gradients in Timber by Measurements of Capacitance Using a Multiple-Electrode Arrangement, 11/12:27-32 (No. 9084).

Jensen, K. and G. Pompelli, Marketing and Business Assistance Needs Perceived by Tennessee Forest Products Firms, 7/8:48-54 (No. 9026).

Jung, H.-S., see Lee, N.-H.

K

Kaczmar, P., see Ahmet, K.

Kärki, T., Species, Furniture Type, and Market Factors Influencing Furniture Sales in Southern Germany, 4:85-90 (No. 8984).

Katabian, M., see Sellers, T., Jr.

Keith, J., see De Groot, R.C.

Kellogg, L.D., see Han, H.-S.

Kimberley, M., see Gazo, R.

King, S.A. and D.K. Lewis, Manufacturing Solid Wood Products From Used Utility Poles: An Economic Feasibility Study, 11/12: 69-78 (No. 9021).

Kluender, R., R. Weih, M. Corrigan, and J. Pickett, Assessing the Operational Cost of Streamside Management Zones, 2:30-34 (No. 8782).

Kluender, R., R. Weih, M. Corrigan, and J. Pickett, The Use of a Geographic Information System in Harvest Landing Location for Ground-Based Skidding Operations, 3:87-92 (No. 8791).

Kumar, L., see Steele, P.H.

Kutscha, N.P., see Floyd, S.L.

L

Lang, E.M., see Bejo, L.

Lantz, S.F., see Falk, R.H.

Lavery, M.R. and M.R. Milota, VOC Emissions From Douglas-fir: Comparing a Commercial and a Laboratory Kiln, 7/8:39-47 (No. 8958).

Layton, H.D., see Rippy, R.C.

Leavengood, S., see Pearson, E.G.

LeDoux, C.B., Matching Skidder Size to Wood Harvested to Increase Hardwood Fiber Availability: A Case Study, 10:86-90 (No. 9049).

Lee, N.-H. and K. Hayashi, Effect of End-Covering and Low Pressure Steam Explosion Treatment on Drying Rate and Checking During Radio-Frequency/Vacuum Drying of Japanese Cedar Log Cross Sections, 2:73-78 (No. 8916).

Lee, N.-H. and H.-S. Jung, Comparison of Shrinkage, Checking, and Absorbed Energy in Impact Bending of Korean Ash Squares Dried by a Radio-Frequency/Vacuum Process and a Conventional Kiln, 2:69-72 (No. 8867).

Leichti, R.J., see Anderson, M.E.

Lemaster, R.L., L. Lu, and S. Jackson, The Use of Process Monitoring Techniques on a CNC Wood Router. Part 1. Sensor Selection, 7/8:31-38 (No. 8917).

Lemaster, R.L., L. Lu, and S. Jackson, The Use of Process Monitoring Techniques on a CNC Wood Router. Part 2. Use of a Vibration Accelerometer to Monitor Tool Wear and Workpiece Quality, 9:59-64 (No. 8918).

Lewis, D.K., see King, S.A.

Lewis, V.R., A.B. Power, and M.I. Haverty, Laboratory Evaluation of Microwaves for Control of the Western Drywood Termite, 5:79-87 (No. 9006).

Liao, T.M.-Y., see Chen, C.-M.

Lin, F.-C., see Zhang, J.

Lopez-Anido, R., D.J. Gardner, and J.L. Hensley, Adhesive Bonding of Eastern Hemlock Glulam Panels With E-Glass/Vinyl Ester Reinforcement, 11/12:43-47 (No. 9073).

Lorenz, L.F., see Baumann, M.G.D.

Lovell, R., see Barry, A.

Lu, L., see Lemaster, R.L.

Luzadis, V.A., see Carroll, M.E.

Lum, C., see Troughton, G.E.

Luppold, W., J. Baumgras, and G. Barrett, Characteristics of the Eastern "Grade" Hardwood Sawmilling Industry, 9:23-27 (No. 9065).

Luppold, W.G. and J.E. Baumgras, Analysis of Changes in Eastern National Forest Timber Sales Between 1985 and 1997, 1:87-93 (No. 8952).

Luppold, W.G. and W.H. McWilliams, Issues Affecting the Interpretation of Eastern Hardwood Resource Statistics, 4:21-24 (No. 9005).

Lynch, D.L., see Mackes, K.H.

M

Mackes, K.H. and D.L. Lynch, An Assessment of Pallet Lumber Supply and Manufacturing in Colorado, 4:77-80 (No. 8938).

Mangun, J.C. and J.E. Phelps, Profiling Existing Markets: The Illinois Secondary Solid Wood Products Industry, 5:55-60 (No. 9003).

Mankowski, M. and J.J. Morrell, Incidence of Wood-Destroying Organisms in Oregon Residential Structures, 1:49-52 (No. 8935).

Mano, E.B., see Barbosa, A.P.

McAlister, R.H., H.R. Powers, and W.D. Pepper, Mechanical Properties of Stemwood and Limbwood of Seed Orchard Loblolly Pine, 10:91-94 (No. 8995).

McCarl, B.A., see Alig, R.J.

McConchie, D., see Gazo, R.

McWilliams, W.H., see Luppold, W.G.

Mengeloglu, F. and D.J. Gardner, Recycled CCA-Treated Lumber in Flakeboards: Evaluation of Adhesives and Flakes, 2:41-45 (No. 8925).

Miller, G.D., Jr., see Sellers, T., Jr.

Milota, M.R., Emissions From Wood Drying: The Science and the Issues, 6:10-20 (No. 9056).

Milota, M.R., Warp and Shrinkage of Hem-fir Stud Lumber Dried at Conventional and High Temperatures, 11/12:79-84 (No. 9038).

Milota, M.R., see Lavery, M.R.

Mooney, S.T., K.D. Boston, and W.D. Greene, Production and Costs of the Chambers Delimbinator in First Thinning of Pine Planatations, 4:81-84 (No. 9001).

Moore, P., Trees are the Answer, 10:12-19 (No. 9059).

Morita, T., J.Y. Sheikh-Ahmad, K. Banshoya, T. Tsutsumoto, and Y. Murase, On the Cutting Performance of Diamond-Coated Cemented Carbide Tools Pretreated With Murakami/H_2O_2-H_2SO_4 Solution, 1:67-73 (No. 8971).

Morrell, J.J. and R. Rhatigan, Preservative Movement From Douglas-fir Decking and Timbers Treated With Ammoniacal Copper Zink Arsenate Using Best Management Practices, 2:54-58 (No. 8924).

Morrell, J.J., see Anderson, M.E.

Morrell, J.J., see Mankowski, M.

Morrell, J.J., see Rhatigan, R.G.

Moschler, W.W., see Wang, S.

Moseley, C., see Wolfe, R.

Mougel, E., see Alberto, M.M.

Murase, Y., see Morita, T.

N

Newbill, M.A., see Rhatigan, R.G.

Nguyen, N.-K., see Creffield, J.W.

Nicholas, D.D., see Oh, Y.-S.

Nicholls, D.L., see Chen, C.-M.

Norton, J., see De Groot, R.C.

O

Oh, Y.-S., L.S. Sites, T. Sellers, Jr., and D.D. Nicholas, Computerized Dynamic Swellometer Evaluation of Oriented Strand Products, 3:35-38 (No. 8979).

Okkonen, E.A., see Vick, C.B.

Ouis, D., Potential Use of a Piezoelectric Wire Sensor for Monitoring the Bending Vibrations of Logs, 4:61-64 (No. 8855).

P

Pacheco, G., see Abt, R.C.

Pearson, E.G., S. Leavengood, and J.E. Reeb, Comparison of the Absorptive Capacity of Shavings of Western Juniper, Western Redcedar, and Douglas-fir for Animal Bedding, 6:57-60 (No. 9019).

Pepper, W.D., see McAlister, R.H.

Peterson, P., see Bratkovich, S.M.

Phelps, J.E., see Mangun, J.C.

Pickett, J., see Kluender, R.

Pitis, O.T. and R.P. Vlosky, Forest Products Exporting and the Internet: Current Use Figures and Implementation Issues, 10:23-29 (No. 9030).

Pitis, O.T. and R.P. Vlosky, Web Presence of U.S. Primary Wood Products Exporters, 7/8:55-58 (No. 9041).

Pompelli, G., see Jensen, K.

Powell, M.A., J.F. Webber, and R.A. Eaton, Changes in Moisture, Soluble Carbohydrate, and Bacterial Numbers During Water Storage of Pine, 3:74-80 (No. 8994).

Power, A.B., see Lewis, V.R.

Powers, H.R., see McAlister, R.H.

Preston, A.F., Wood Preservation: Trends of Today That Will Influence the Industry Tomorrow, 9:12-19 (No. 9058).

R

Rammer, D., see Falk, R.H.

Reeb, J.E., see Pearson, E.G.

Ren, H., see Dippon, J.

Rhatigan, R.G., P.F. Schneider, M.A. Newbill, and J.J. Morrell, Capping and Chemical Treatment of Douglas-fir Piling to Prevent Pile Top Decay: A 13-Year Test, 7/8:66-70 (No. 8813).

Rhatigan, R., see Morrell, J.J.

Riddiough, S., see Ahmet, K.

Rippy, R.C., F.G. Wagner, T.M. Gorman, H.D. Layton, and T. Bodenheimer, Stress-Wave Analysis of Douglas-fir Logs for Veneer Properties, 4:49-52 (No. 8966).

Roadcap, C.A., P.M. Smith, and R.P. Vlosky, EDI and Barcoding in the Homecenter Industry: 1992 vs. 1998, 9:32-38 (No. 9051).

Roliadi, H., C.Y. Hse, E.T. Choong, and T.F. Shupe, Decay Resistance of Out-of-Service Utility Poles as Related to the Distribution of Residual Creosote Content, 11/12: 64-68 (No. 9037).

Roliadi, H., C.Y. Hse, E.T. Choong, and T.F. Shupe, Gluability of Out-of-Service Utility Poles, 10:76-81 (No. 9062).

Rosowsky, D.V., see Cai, Z.

Ross, R.J., see Cai, Z.

S

Saileela, B., see Diehl, S.V.

Sasaki, Y., see Ayarkwa, J.

Schmalzl, K.J., see Crawford, D.M.

Schmidt, E.L., see Wallace, B.L.

Schneider, P.F., see Rhatigan, R.G.

Sellers, T., Jr., D.L. Butler, C.L. Griffin, D.E. Headley, and G.D. Miller, Jr., Laboratory Apparatus for Applying Air-Sprayed Powdered Adhesive, 5:88-90 (No. 9007).

Sellers, T., Jr., G.D. Miller, Jr., and M. Katabian, Recycled Thermoplastics Reinforced With Renewable Lignocellulosic Materials, 5:24-28 (No. 8991).

Sellers, T., Jr., see Oh, Y.-S.

Senft, J.F., see Evans, J.W., II.

Serrano, J.R. and D. Cassens, Pallet and Component Parts From Small-Diameter Red Oak Bolts, 3:67-73 (No. 8725).

Sharp, D.J., S.K. Suddarth, and C. Beaulieu, Length Effect in Prefabricated Wood I-Joists, 5:29-42 (No. 8849).

Sheikh-Ahmad, J.Y., see Morita, T.

Shmulsky, R., End-Grain Influence on VOC Emissions From Kiln-Drying Loblolly Pine, 5:21-23 (No. 9044).

Shmulsky, R., Influence of Drying Schedule on VOC Emissions From Kiln-Drying Loblolly Pine Lumber, 4:45-48 (No. 8894).

Shmulsky, R., Influence of Lumber Dimension on VOC Emissions From Kiln-Drying Loblolly Pine Lumber, 3:63-66 (No. 9043).

Shmulsky, R. and L.L. Ingram, Jr., Empirical Prediction of VOC Emissions From Drying Southern Yellow Pine Lumber, 6:61-63 (No. 9024).

Shmulsky, R., see Ingram, L.L., Jr.

Shmulsky, R., see Steele, P.H.

Shupe, T.F. and M.A. Dunn, The Formosan Subterranean Termite in Louisiana: Implications for the Forest Products Industry, 5:10-18 (No. 9055).

Shupe, T.F., see Dunn, M.A.

Shupe, T.F., see Roliadi, H.

Sikanen, L., see Eronen, J.

Sites, L.S., see Oh, Y.-S.

Smith, P.M., see Roadcap, C.A.

Smith, R.L., W.E. Spradlin, D.R. Alderman, Jr., and E. Cesa, Perceptions of Wood in the Highway Infrastructure Market, 6:23-31 (No. 9016).

Smith, R.L., see Alderman, D.R., Jr.

Soltis, L.A., see Cai, Z.

Spradlin, W.E., see Smith, R.L.

Steele, P.H., L. Kumar, and R. Shmulsky, Differentiation of Knots, Distorted Grain, and Clear Wood by Radio-Frequency Scanning, 3:58-62 (No. 8981).

Stewart, H.A., see Wiltcher, D.

Suddarth, S.K., see Sharp, D.J.

Sutton, W.R.J., Wood in the Third Millennium, 1:12-21 (No. 9052).

Syers, T.L., see Crawford, D.M.

T

Takahashi, T., see Tsuchikawa, S.

Taylor, F.W., see Ingram, L.L., Jr.

Templeton, M.C., see Ingram, L.L., Jr.

Thomas, R.E., see Gatchell, C.J.

Tomlin, R., see Ahmet, K.

Tracy, J.M., SIPs: Overcoming the Elements, 3:12-18 (No. 9054).

Troughton, G.E. and C. Lum, Pilot Plant Evaluation of Steam-Injection Pressing for LVL and Plywood Products, 1:25-28 (No. 8972).

Tsuchikawa, S., T. Takahashi, and S. Tsutsumi, Nondestructive Measurement of Wood Properties by Using Near-Infrared Laser Radiation, 1:81-86 (No. 8871).

Tsutsumi, S., see Tsuchikawa, S.

Tsutsumoto, T., see Morita, T.

U

Unnanon, K., see Cormier, D.

Uusitalo, J., see Eronen, J.

V

Vick, C.B. and E.A. Okkonen, Durability of One-Part Polyurethane Bonds to Wood Improved by HMR Coupling Agent, 10:69-75 (No. 9031).

Vlosky, R.P., USDA Forest Service, Bureau of Land Management, and State Forester Perspectives on Certification, 3:21-27 (No. 8823).

Vlosky, R.P., see Dunn, M.A.

Vlosky, R.P., see Dupuy, C.A.

Vlosky, R.P., see Pitis, O.T.

Vlosky, R.P., see Roadcap, C.A.

Vlosky, R.P., see Wu, Q.

W

Wagner, F.G., see Rippy, R.C.

Wagner, J.E., see Carroll, M.E.

Walker, E.S., see Gatchell, C.J.

Wallace, B.L. and E.L. Schmidt, Use of an Air Pressure Method for Detection and Mapping of Highly Permeable Ponderosa Pine, 7/8:71-74 (No. 8986).

Wang, S. and P.M. Winistorfer, The Effect of Species and Species Distribution on the Layer Characteristics of OSB, 4:37-44 (No. 8989).

Wang, S., P.M. Winistorfer, W.W. Moschler, and C. Helton, Hot-Pressing of Oriented Strandboard by Step-Closure, 3:28-34 (No. 8999).

Wasson, L.L., see Diehl, S.V.

Watkins, J.B., see Crawford, D.M.

Webber, J.F., see Powell, M.A.

Weih, R., see Kluender, R.

West, C.D., see Bumgardner, M.S.

Wilson, A.C., F.E. Woeste, and D.J. Dolan, Wood Floor Vibrational Performance as Affected by MSR vs. VSR Lumber E-Distribution, 4:53-60 (No. 8852).

Wiltcher, D., H. Borazjani, S.V. Diehl, and H.A. Stewart, Composting of Phenolic-Bonded Softwood Plywood Waste, 10:82-85 (No. 9046).

Wingate-Hill, R., see Evans, P.D.

Winistorfer, P.M., see Wang, S.

Woeste, F.E., see Wilson, A.C.

Wolfe, R., Research Challenges for Structural Use of Small-Diameter Round Timbers, 2:21-29 (No. 8963).

Wolfe, R. and C. Moseley, Small-Diameter Log Evaluation for Value-Added Structural Applications, 10:48-58 (No. 8996).

Woodward, B., see De Groot, R.C.

Wu, Q. and R.P. Vlosky, Panel Products: A Perspective From Furniture and Cabinet Manufacturers in the Southern United States, 9:45-50 (No. 8993).

X

Xu, W., Influence of Percent Alignment and Shelling Ratio on Linear Expansion of Oriented Strandboard: A Model Investigation, 7/8:88-93 (No. 9012).

Xu, W., Influence of Percent Alignment and Shelling Ratio on Modulus of Elasticity of Oriented Strandboard: A Model Investigation, 10:43-47 (No. 9023).

Y

Yin, R., T.G. Harris, and B. Izlar, Why Forest Products Companies May Need to Hold Timberland, 9:39-44 (No. 9036).

Z

Zhang, G.-Z., see Baumann, M.G.D.

Zhang, J., F.-C. Lin, C. Eckelman, and H. Gibson, A Structural Design Model For Sofa Seat Frames Equipped With Sinusoidal-Type Springs, 3:49-57 (No. 8907).

Zoulalian, A., see Alberto, M.M.

Statement of Ownership, Management, and Circulation
(Act of August 12, 1970; Section 3685, Title 39, United States Code)

1. Date of filing: October 12, 2000.
2. Title of publication: *FOREST PRODUCTS JOURNAL.*
3. Frequency of issue: 10 times a year.
4. Location of known office of publication: 2801 Marshall Court, Madison, Wi 53705.
5. Location of the headquarters or general business offices of the publishers: Same.
6. Names and addresses of publisher and editor: Publisher, Forest Products Society - A.B. Brauner, Executive Vice President and Treasurer, 2801 Marshall Court, Madison, WI 53705; Editor, Erin Bosch, same address.
7. Owner, name and address: Forest Products Society, 2801 Marshall Court, Madison, WI 53705.
8. Known bondholders, mortgages, and other security holders owning or holding 1% or more of total amount of bonds, mortgages, or other securities: None.
9. The purpose, function, and nonprofit status of this organization and the exempt status for Federal income tax purposes have not changed during the preceding 12 months.
10. Extent and nature of circulation:

	Average No. of Copies Each Issue During Preceding 12 Months	No. of Copies of Single Issue Nearest Filing Date
A. Total no. of copies printed (net press run)	2860	2850
B. Paid circulation:		
1. Sales through dealers and carriers, street vendors, and counter sales	512	533
2. Mail subscriptions	2013	2015
C. Total paid circulation	2525	2548
D. Free distribution	116	116
E. Total distribution (sum of C and D)	2641	2664
F. Office use, left-over, unaccounted, spoiled after printing	219	186
G. Total (sum of E and F, should equal net press run in A)	2860	2850
H. Percent paid and/or requested circulation	95.6%	95.6%

I certify that the statements made by me are correct and complete.
A.B. Brauner, Executive Vice President and Treasurer